

SET-UP SHEET

AIR TEMP F° °

LAPS

BEST LAP TIME in LAP

TRACK SIZE
☐ OPEN ☐ MEDIUM ☐ TIGHT

TRACK TRACTION
☐ HIGH ☐ MEDIUM ☐ LOW

DIFFERENTIAL OIL	
FRONT	REAR
☐ STD	☐ STD
wt.	wt.
DIFFERENTIAL CASE	
☐ PLASTIC	☐ ALUM

CLUTCH	
	SHOE
	SPRING
mm	

GEARING			
SPUR GEAR		T &	
PINION GEAR		T &	

TIRES	
FRONT TYPE	
COMPOUND	
INSERT FOAM	
REAR TYPE	
COMPOUND	
INSERT FOAM	

ENGINE	
TYPE	
PORT	
PLUG	
☐ NORMAL ☐ TURBO	
HEAD CLEARANCE	
PIPE	
FUEL BRAND	

NAME RACE DATE

TRACK CITY/COUNTRY TRACK CONDITION

FRONT

CASTER BLOCK
☐ 6° ☐ 8°
☐ 10° ☐ 12°

DROOP mm

INSERT NR.

☐ ☐ ☐ ☐

STEERING BAR

☐ X3S-44 (OPT)

RIDE HEIGHT

mm

SWAY BAR

mm

CAMBER ANGLE

°

TOE ANGLE

°

SHOCK FRONT

SHOCK LENGHT mm

OIL wt.

PISTON mm

SPRING

SHOCK LENGHT mm

REAR

DROOP mm

INSERT NR.

☐ ☐ ☐ ☐

WHEELBASE SHIMS

☐ 0mm ☐ 2mm
☐ 2.5mm ☐ 4.5mm

SHOCK REAR

SHOCK LENGHT mm

OIL wt.

PISTON mm

SPRING

SHOCK LENGHT mm