

Race		Name	
Track		Date	
Temperature	C	F	Best Lap Time

Steering Rod
TOE In Out

mm

mm
ALU C-Hub Shim

0.8mm
1.9mm

Anti-Roll

mm

FF-2mm

FR-2mm

Length

Shock Body

13.0mm

12.8mm

Pom Shim

0.36mm

Oil

Pistons

Downstop

Up stop

Length

O Rings

Holes

Shim

Shim

mm

mm

mm

mm

transparent

Red

Caster

5°

8°

11°

Camber	
Ride Height	mm
TOE In Out	
Type R Shock Spring	

[illegible]

Motor	T
Spur Gera	T
Pinion	T
Esc	

Battery Size ☐ Std. Short
☐ Low Short

Front

Radio System

Tire	ST-DR
------	-------

Inserts ST-EXP

Wheels	ST-Speed
--------	----------

Rear	Radio System
------	--------------

Tire	TH-DR
------	-------

Inserts TH-EXP

Wheels	TH-Speed
--------	----------

--	--

[illegible]

Body	
------	--

[illegible]

001 ☐

002 ☐

003 ☐

A ☐

B ☐

FR. RACING

mm

Rear Hub Shim

mm

Rear Hub Shim

Apply CA Glue if needed

FRONT ☐ REAR ☐

 



Front
Oil # _____



Central Differential
Oil # _____



Rear
Oil # _____



2/Gear
4/Gear

Cut pins

FRONT	REAR
	

Chassis Flex

☐ Kit Chassis

FRONT

☐ Op Chassis

SCREW USED _____ SCREW NOT USE X

