# SET-UP SHEET

X1'25 SET-UP SHEET VER.1 ©XRAY

XRAY X1'25

| | |
|---|---|
| RACE | Czech summer masters |
| TRACK | Hudy arena asphalt |
| NAME | Tomas Liptak |
| DATE | 23.-24.5.2026 |


| QUAL POSITION | FINAL POSITION | BEST LAPTIME | LAPS | TIME |
|---|---|---|---|---|
| 1 | 1 | 20,43 /sec | 15 | /5:12,84 |

## TRACK

| | | | |
|---|---|---|---|
| TRACK SURFACE | ☐ CARPET | ☒ ASPHALT | |
| TRACK LAYOUT | ☐ TECHNICAL | ☐ MIXED | ☐ FAST |
| TRACTION | ☐ LOW | ☒ MEDIUM | ☐ HIGH |

CENTER SHOCK ☒ — CENTER SHOCK DAMPENER — ☐ CENTER TUBE





| | | | |
|---|---|---|---|
| SHOCK OIL | 1000 /cSt | TUBE OIL | /cSt |
| SHOCK REBOUND | /% | | |

## BUMP SPRING




☒ CONICAL-PROGRESSIVE 1,5-1,6 /C

STRAIGHT-LINEAR ☐ /C



## SIDE DAMPING




OIL 10000 /cSt

## TIRES

RUBBER ☐ ☒ FOAM

| FRONT | | REAR |
|---|---|---|
| Hudy | TIRES | Hudy |
| | DIAMETER /mm | |
| H. asphalt 106262 | ADDITIVE | H. asphalt 106262 |
| 50min | ADDITIVE TIMING | 50min |
| 5min | WIPE OFF TIME | 5min |



SIDE WALL GLUE DIA. /mm

SIDE GLUE DIA. /mm

ADDITIVE AREA full /mm

## TRANSMISSION

| GEAR DIFF | SOLID AXLE | BALL DIFF |
|---|---|---|
| ☒ | ☐ | ☐ |
| OIL 3000 /cSt | | ☐ ☐ ☐ ☐ ☐ LOOSE MEDIUM TIGHT |

## GEARING

(spur) ÷ (pinion) = FDR

| SPUR GEAR /T | PINION /T | FINAL DRIVE RATIO |
|---|---|---|
| 84 | 34 | |

## ELECTRONICS

| | |
|---|---|
| MOTOR | HW G4R 21.5T |
| SPEEDO | Elceram oxide |
| SERVO | |
| BATTERIES | Nosram 4200 |

## BODY

montech F22

## COMMENTS

