SET-UP SHEET

XRAY XT2'28

RACE	Austrian Nats round 4
TRACK	RMC Wien - Ebreichsdorf
NAME	Bartek Zalewski
DATE	
COUNTRY	
CITY	

QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
1		26.8 /sec	/	

TRACK

SIZE	☐ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	☐ ☐ ☐ ☐ ☒ ☐ ☐ ☐ ☐		
	VERY-LOW	MEDIUM	VERY-HIGH
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ CLAY	☐ CARPET	☒ ASTRO
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED	☒ DRY
	☐ GLUED	☐ DUSTY	☐ LOAMY	☐ WET

TRANSMISSION

BALL DIFF ☐ GEAR DIFF ☒ ACTIVE DIFF ☐

DIFFERENTIAL OIL 5 cSt — 60° 90° 120°

SATELITE GEARS COMPOSITE ☐ ☒ STEEL GEARS 2 ☐ ☒ 4

SLIPPER mm ☐ SOLID AXLE

SLIPPER PADS KIT ☐

GEARING

PINION	SPUR GEAR
19 T	78 T

GEAR BOX

TYPE: FRONT LCG 3G ☒ ☐ 5G — HARDNES: KIT ☒ ☐ GRAPHITE

SHOCKS

FRONT		REAR
4 dot buggy	SPRINGS	3 dot buggy
cSt	OIL	cSt
2 HOLES ☒	☒ ø1.6mm ☐ ø1.8mm	2 HOLES ☒
HOLES	ø mm / ø 2.0 mm	HOLES
KIT ALU CAP ALU KIT		
Previous 0 -1 -1		-1 -1 0 Previous
Piston 2.0 ☐ ☒ 2.5 KIT ☒ ☐ Precis.		Piston 2.5 ☒ ☐ 2.0 Precis. ☐ ☒ KIT
Downstop shim INSERT UNDER PISTON 0 mm		mm 0 Downstop shim INSERT UNDER PISTON
Length 22.5 mm		mm 29 Length
Upstop shim INSERT ABOVE COLLAR 0 mm		mm 0 Upstop shim INSERT ABOVE COLLAR
0mm ☐ -2mm ☒ -4mm -6mm COMP. ☒ ALU ☐	COLLAR	0mm ☐ -2mm ☒ -4mm -6mm COMP. ☒ ALU ☐
☐ ☐ ☒ +4mm +2mm 0mm	BALL JOINT	☐ ☐ ☒ 0mm +2mm +4mm

ANTI ROLL BAR

FRONT	THICKNESS	REAR
1.6 /mm		1.3 /mm

TIRES

FRONT		REAR
JC	BRAND	JC
pink	COMPOUND	pink
std	INSERTS	std
Xray	WHEELS	Xray

ELECTRONICS

MOTOR	CAYOTE 6.0	CREST X EVO	SPEEDO
SERVO	Savox	Cayote 4600	BATTERY

BODY

kit ☐ LIGHT

TOTAL WEIGHT

/g

COMMENT

4 dot buggy(368194)
3 dot buggy(368293)

FRONT / REAR — APPLIED ◉ ☒ APPLIED

CASTER BLOCK: MEDIUM ☒ HARD ☐ GRAPHITE ☐ ALU ☐ STEER. ANGLE SCREW ☐

LONGER BUSHINGS: UP ☐ DOWN ☒

ALU C-HUB: UP /mm DOWN /mm

STEERING BLOCK: MEDIUM ☒ HARD ☐ GRPHITE ☐ ALU ☐

CAMBER LINK LOCATION

UPPER SHOCK POSITION

LOWER SHOCK POSITION

SHIM 1 mm

SHIM 0 /mm

SHIM 3 mm

SHIM mm

LOWER SHOCK POSITION

REAR UPRIGHT: ☒ MEDIUM - KIT ☐ HARD ☐ GRAPHITE ☐ ALU — ☒ HIGH ☐ LOW

#325341 ADJ. DRIVE AXLE

ARM MOUNT

0° ☐ KIT
0° ☒ ALU
-3° ☐ ALU
+3° ☐ ALU
0° ☐ BRASS
TOTAL KICK-UP°

STEERING BUMP STEER SHIM 1 /mm

ACKERMANN SHIM 0 /mm

CASTER BUSHINGS 0° 2.5° 5° ☐ ☐ ☒

KICK-UP°

ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP

FRONT

HIGH

WING

HIGH ☐
LOW ☒
OTHER /mm

FRONT TOE / OFFSET / WHEELBASE / ROLL CENTER

FRONT TOE -2 °

OUT

OFFSET

WHEELBASE 0 /mm

ROLL CENTER: KIT ☐ ALU ☒

STEERING

PLATE: KIT ☐ ALU ☒
ARMS: KIT ☒ ALU ☐

EXTENSION

1 DOT ☐
2 DOTS ☐
3 DOTS ☒

SERVO BRACE

YES ☐ ☒ NO

SERVO POSITION 1 2

SIDE BRACES

KIT ☒ ☐ GRAPHITE

BATTERY PLACEMENT

LONG SIDE FRONT ☐ ☐ ☒ LONG SIDE REAR

BATTERY SIZE

☐ STD. SHORT
☐ LOW SHORT

1 2 3 4 5 6 7 8

COOLING

FRONT ☐ ☐ REAR

REAR TOE 3 °

IN

MOTOR PLATE

1 DOT-KIT ☒

OFFSET 6

WHEELBASE 2 /mm

ROLL CENTER

ALU - KIT ☒
GRAPHITE ☐
COMP. ☐

REAR

REAR ROLL CENTER SUSPENSION HOLDERS

RF 0.5° ☐ ☐ 1°

RR 0.5° ☐ ☐ 1° — XRAY 3° — SHIM /mm SHIM

3° 1°

RR 0.5° ☐ ☐ 1° — XRAY 1° — SHIM /mm SHIM

FRONT CAMBER / GLUING SIDEWALL

FRONT CAMBER 2 /°

GLUING SIDEWALL YES ☐ ☒ NO

RIDE HEIGHT 18.5 /mm

RIDE HEIGHT #107721 GAUGE

DIFF HEIGHT

19 /mm RIDE HEIGHT

REAR CAMBER 2 /°

ARM MOUNT BALANCE

#293085 HUDY Pure Tungsten Weight - 10g.

FRONT ARM

MEDIUM ☒
HARD ☐
GRAPHITE ☐

ARM TYPE

SOLID ☐
OPEN ☐

SERVO WEIGHT

STANDARD ☒
LOW PROFILE ☐

BALANCE /g

BALANCE 30 /g

BALANCE 50 /g

FRONT CHASSIS FLEX

ELECTRONICS PLATE

NO ☐ GRAPHITE ☐ WEIGHT ☒

REAR CHASSIS FLEX

LOWER ECCENTRIC SHOCK BALL

FRONT ☒ ☐ REAR

CHASSIS BRACE

3G ☒
5G ☐

ARM SHIM 2 /mm

REAR ARM

MEDIUM ☒
HARD ☐
GRAPHITE ☐