SET-UP SHEET

XRAY XT2'28

RACE	Austrian Nats round 4		
TRACK	RMC Wien - Ebreichsdorf		
NAME	Hupo Hönigl	DATE	
COUNTRY		CITY	

QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
1		26.8 /sec	/	

TRACK

SIZE	☐ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	☐ ☐ ☐ ☐ ☒ ☐ ☐ ☐ ☐		
	VERY-LOW	MEDIUM	VERY-HIGH
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ CLAY	☐ CARPET	☒ ASTRO
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED	☒ DRY
	☐ GLUED	☐ DUSTY	☐ LOAMY	☐ WET

TRANSMISSION

BALL DIFF ☐	GEAR DIFF ☒	ACTIVE DIFF ☐	
DIFFERENTIAL	OIL 5K cSt	60° 90° 120°	
SATELITE GEARS	COMPOSITE ☐	☒ STEEL	GEARS 2 ☐ ☒ 4
SLIPPER	mm	☐ SOLID AXLE	
SLIPPER PADS	KIT ☐		

GEARING

PINION	SPUR GEAR
19 T	78 T

GEAR BOX

TYPE	HARDNES
FRONT LCG 3G ☒ ☐ 5G	KIT ☒ ☐ GRAPHITE

SHOCKS

FRONT		REAR
4 dot buggy	SPRINGS	3 dot buggy
cSt 400	OIL	350 cSt
2 HOLES ☒	☐ ø1.6mm ☒ ø1.8mm	2 HOLES ☒
HOLES	ø mm / ø 2,0 mm	HOLES
KIT ☒ ALU ☐	CAP	ALU ☐ KIT ☒
Previous 0 ☒ -1 ☐ -1 ☐		-1 ☐ -1 ☐ 0 ☐ Previous
Piston 2.0 ☐ 2.5 ☒ KIT ☒ Precis. ☐		2.5 ☒ 2.0 ☐ Piston Precis. ☐ KIT ☒
Downstop shim INSERT UNDER PISTON 0 mm		mm 0 Downstop shim INSERT UNDER PISTON
Length 22,5 mm		mm 29 Length
Upstop shim INSERT ABOVE COLLAR 0 mm		mm 0 Upstop shim INSERT ABOVE COLLAR
0mm ☐ -2mm ☒ -4mm ☐ -6mm ☐ COMP. ☒ ALU ☐	COLLAR	0mm ☐ -2mm ☒ -4mm ☐ -6mm ☐ COMP. ☐ ALU ☐
☐ ☐ ☒ +4mm +2mm 0mm	BALL JOINT	☐ ☐ ☒ 0mm +2mm +4mm

ANTI ROLL BAR

FRONT	THICKNESS	REAR
1.6 /mm		1.3 /mm

TIRES

FRONT		REAR
JC	BRAND	JC
pink	COMPOUND	pink
std	INSERTS	std
Xray	WHEELS	Xray

ELECTRONICS

MOTOR	Cayote 6,0	Nitride G2	SPEEDO
SERVO	H-Speed	Cayote 4600	BATTERY

BODY	TOTAL WEIGHT
kit ☐ LIGHT	/g

COMMENT

FRONT / REAR

APPLIED ◉ ☒ APPLIED

CASTER BLOCK: MEDIUM ☒ / HARD ☐ / GRAPHITE ☐ / ALU ☐ / STEER. ANGLE SCREW ☐

LONGER BUSHINGS: UP ☐ / DOWN ☒

ALU C-HUB: UP /mm / DOWN /mm

STEERING BLOCK: MEDIUM ☒ / HARD ☐ / GRPHITE ☐ / ALU ☐

CAMBER LINK LOCATION

UPPER SHOCK POSITION

LOWER SHOCK POSITION

SHIM 1 mm

SHIM 0 mm

LOWER SHOCK POSITION

SHIM 0 /mm

SHIM 3 mm

REAR UPRIGHT: MEDIUM - KIT ☒ / HARD ☐ / GRAPHITE ☐ / ALU ☐

HIGH ☒ / LOW ☐

#325341 ADJ. DRIVE AXLE

ARM MOUNT

0° ☐ KIT
0° ☒ ALU
-3° ☐ ALU
+3° ☐ ALU
0° ☐ BRASS
TOTAL KICK-UP°

STEERING BUMP STEER SHIM 1 /mm

ACKERMANN SHIM 0 /mm

CASTER BUSHINGS: 0° ☐ 2.5° ☐ 5° ☒

KICK-UP°

ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP

FRONT

HIGH

WING: HIGH ☐ / LOW ☒ / OTHER /mm

FRONT TOE -2 °

OUT

OFFSET

WHEELBASE 0 /mm

ROLL CENTER: KIT ☐ / ALU ☒

STEERING: PLATE ☐ KIT ☒ ALU / ARMS ☒ KIT ☐ ALU

EXTENSION: 1 DOT ☐ / 2 DOTS ☐ / 3 DOTS ☒

SERVO BRACE: YES ☐ ☒ NO

SERVO POSITION 1 2

REAR TOE 3 °

IN

BATTERY PLACEMENT: LONG SIDE FRONT ☐ / ☒ LONG SIDE REAR

MOTOR PLATE: 1 DOT-KIT ☒

OFFSET 6

WHEELBASE 2 /mm

BATTERY SIZE: ☐ STD. SHORT / ☐ LOW SHORT

ROLL CENTER: ALU - KIT ☒ / GRAPHITE ☐ / COMP. ☐

SIDE BRACES: KIT ☒ ☐ GRAPHITE

COOLING: FRONT ☐ ☐ REAR

1 2 3 4 5 6 7 8

REAR

REAR ROLL CENTER SUSPENSION HOLDERS

RF 0.5° ☐ 1°

RR 0.5° ☐ 1° XRAY 3° SHIM /mm SHIM

3° 1°

RR 0.5° ☐ 1° XRAY 1° SHIM /mm SHIM

FRONT CAMBER -1,5 /°

GLUING SIDEWALL: YES ☐ ☒ NO

RIDE HEIGHT 18,5 /mm

RIDE HEIGHT #107721 GAUGE

DIFF HEIGHT

-1,5 /° **REAR CAMBER**

18,5 /mm RIDE HEIGHT

ARM MOUNT BALANCE

#293085 HUDY Pure Tungsten Weight - 10g.

SERVO WEIGHT: STANDARD ☒ / LOW PROFILE ☐

BALANCE /g

BALANCE 30 /g

BALANCE 50 /g

LOWER ECCENTRIC SHOCK BALL: FRONT ☒ ☐ REAR

CHASSIS BRACE: 3G ☒ / 5G ☐

ARM SHIM 2 /mm

FRONT ARM: MEDIUM ☒ / HARD ☐ / GRAPHITE ☐

ARM TYPE: SOLID ☒ / OPEN ☐

FRONT CHASSIS FLEX

ELECTRONICS PLATE: NO ☐ GRAPHITE ☐ WEIGHT ☒

REAR CHASSIS FLEX

REAR ARM: MEDIUM ☒ / HARD ☐ / GRAPHITE ☐