SET-UP SHEET

XRAY X1'27


RACE	Basic for Rubber Carpet
TRACK	
NAME	Team Xray
DATE	
COUNTRY	Slovakia
CITY	Trencin

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME /sec	LAPS	TIME
				/	


TRACK

TRACK SURFACE		☒ CARPET	☐ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☒ MIXED	☐ FAST
TRACTION	☐ LOW	☒ MEDIUM	☐ HIGH

CENTER SHOCK ☒ — CENTER SHOCK DAMPENER — ☐ CENTER TUBE



OIL 1000 /cSt — REBOUND 0 /%



OIL /cSt

BUMP SPRING

☒ CONICAL-PROGRESSIVE — Silver /C

STRAIGHT-LINEAR ☐ /C


SIDE DAMPING



OIL /cSt

TIRES

FRONT		REAR
RUBBER ☒ FOAM ☐		
	TIRES	
	DIAMETER /mm	
	ADDITIVE	
	ADDITIVE TIMING	
	WIPE OFF TIME	
Timing: / Temp.:	TIRE WARMERS	Timing: / Temp.:



TRANSMISSION

GEAR DIFF	SOLID AXLE	BALL DIFF
☒	☐	☐
OIL 3000 /cSt		☐ ☐ ☐ ☐ ☐ LOOSE MEDIUM TIGHT

GEARING

(spur) ÷ (pinion) = FDR

SPUR GEAR /T — PINION /T — FINAL DRIVE RATIO

ELECTRONICS

MOTOR	
SPEEDO	
SERVO	
BATTERIES	

COMMENTS

