SET-UP SHEET

XRAY X1'27


RACE	Basic for Foam Carpet
TRACK	
NAME	Team Xray
DATE	
COUNTRY	Slovakia
CITY	Trencin

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME /sec	LAPS	TIME
				/	


TRACK

TRACK SURFACE		[X] CARPET	[ ] ASPHALT
TRACK LAYOUT	[ ] TECHNICAL	[X] MIXED	[ ] FAST
TRACTION	[ ] LOW	[X] MEDIUM	[ ] HIGH

CENTER SHOCK [X] — CENTER SHOCK DAMPENER — [ ] CENTER TUBE



OIL 1000 /cSt — REBOUND 0 /%



OIL /cSt

BUMP SPRING




[X] CONICAL-PROGRESSIVE — Silver /C

STRAIGHT-LINEAR [ ] — /C




SIDE DAMPING



OIL /cSt

TIRES

FRONT		REAR
RUBBER [ ] FOAM [X]		
	TIRES	
	DIAMETER /mm	
	ADDITIVE	
	ADDITIVE TIMING	
	WIPE OFF TIME	
Timing: / Temp.:	TIRE WARMERS	Timing: / Temp.:



SIDE WALL GLUE — DIA. /mm

SIDE GLUE — DIA. /mm

ADDITIVE AREA 25 /mm

TRANSMISSION

GEAR DIFF	SOLID AXLE	BALL DIFF
[ ]	[X]	[ ]
OIL /cSt		LOOSE [ ] [ ] MEDIUM [ ] [ ] TIGHT [ ]

GEARING

(spur) ÷ (pinion) = FDR

SPUR GEAR /T — PINION /T — FINAL DRIVE RATIO

ELECTRONICS

MOTOR	
SPEEDO	
SERVO	
BATTERIES	

COMMENTS

