SET-UP SHEET

X4F'26 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'26

RACE	ETS RD1
TRACK	AMC Apeldoorn / RC-Speedracer
NAME	Stefan Schulz
DATE	01.06.2026

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
-	-	-	- /sec	- /	-

TRACK

TRACK SURFACE		☐ CARPET	☒ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED	☒ FAST
TRACTION	☐ LOW	☐ MEDIUM	☒ HIGH

TRANSMISSION

FRONT	REAR
GEAR DIFFERENTIAL - OIL: 200k /cSt	

PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
38	90	4,5

SHOCKS

FRONT		REAR
3,0	XRAY SPRINGS	Soft (2.0)
350	OIL /Cst	350
0	REBOUND %	0
☒ 4 HOLES ☐ PSS	☒ 1.1mm ☐ 1.2mm	☒ 1.1mm ☐ 1.2mm ☒ 4 HOLES ☐ PSS
SHOCK LENGTH 7,5 /mm		7,5 /mm SHOCK LENGTH

1,2	THICKNESS/mm — ANTI-ROLL BAR — THICKNESS/mm	1,3

FRONT		REAR
ETS Ride	TIRES	ETS Ride
MR33 V3	ADDITIVE	MR33 V3
20	ADDITIVE TIMING	20
0	WIPE OFF TIME	0
Timing: 10 Temp.: 80	TIRE WARMERS	Timing: 10 Temp.: 80

SIDE WALL GLUE DIA. - /mm

FRONT TIRES ADDITIVE AREA full /mm

TOTAL WEIGHT	1270 /g	WEIGHT BALANCE	FRONT 67 %	REAR 33 %

MOTOR	HW 17,5T G2.1	TIMING		RPM LIMIT	17500
ESC	HW Just Stock	BATTERIES	Gens Ace 4400		
BODY	Apex	WING	std		

BODY POSITION

/mm Dimension from body post to window bottom line

/mm Dimension from body post to upper holder

WING SIDE PLATE ☒ YES ☐ NO

Dimension from edge to surface /mm

TOP DECK CUTTING

TOP DECK FLEX ☒ 2.0mm ☐ 1.6mm

TOP DECK CUTTING

COMMENTS

FRONT & REAR SUSPENSION

FRONT CASTER ☐ 5° ☒ 4° ☐ 3° — Adjust with eccentric bushings

5 Upper links CASTER

BUMP STEER 2 /mm

HEIGHT 19 /mm

SHIM 1 /mm

REAR CASTER ☐ 0.5° ☐ 1.5° ☒ 2.5° ☐ 3.5° ☐ 4.5° ☐ 5.5° — Adjust with eccentric bushings

2 Upper links CASTER

TOE GAIN 4 /mm

1 /mm FF ☒ — 5,0 /mm RIDE HEIGHT

FR 1 /mm ☒ — ☐ SERVO SAVER ☒ SERVO HORN

2 /mm RF ☒ — 5,2 /mm RIDE HEIGHT

RR 2 /mm ☒

FRONT SUSPENSION

2 /degr. CAMBER — Left=Right

BODY STOP YES ☐ NO ☐ /mm

SHOCK HOLDERS SHIM 2 /mm

FR 1 /mm FF 1 /mm SHIM 2 /mm

FRONT HUB ☐ MEDIUM ☐ HARD ☒ GRAPHITE ☐ ALU

SHIM 0,5 /mm

SUSPENSION FLEX YES ☒ NO ☐ YES ☒ NO ☐

DRIVE SHAFT ☒ 58mm ☐ 59mm ☒ BEARING ☐ BLADE

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge

6 /mm DOWNSTOP

Set with shocks ☒ Set without shocks ☐

REAR SUSPENSION

2 /degr. CAMBER — Left=Right

SHOCK HOLDERS FIXED ☒ ACTIVE ☐ SHIM 2 /mm

RR 1 /mm RF 1 /mm SHIM 2 /mm

REAR HUB ☐ MEDIUM ☐ HARD ☒ GRAPHITE ☐ ALU

SHIM 1 /mm

SUSPENSION FLEX YES ☒ NO ☐ YES ☒ NO ☐

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge

4,4 /mm DOWNSTOP

Set with shocks ☒ Set without shocks ☐

FRONT TOP VIEW REAR

1 TOE OUT — Left=Right

3 TOE IN — Left=Right

DIFF POSITION UP ☒ +1mm ☐ DOWN ☐ STD. ☐

SHIMS /mm — Battery weight plate.

60

ARS LINKS SHIMS 7 /mm

FRONT UPPER ARM C ☐ XS ☐ S ☐ M ☐ LINKS ☒

REAR UPPER ARM C ☐ XS ☐ S ☐ M ☐ LINKS ☒

ACKERMANN BUSHINGS

HUB OFFSET ☒ SHIM /mm

HUB OFFSET ☒ SHIM /mm

FRONT BOTTOM VIEW REAR

WEIGHT LEFT & RIGHT #309826 YES ☒ NO ☐ — 50g + 50g

STEER. LOCK 20 /degr.

T-BRACE ALU ☒ BRASS ☐

BUMPER WEIGHT YES ☐ ☒ NO — 100g

#302055 YES ☐ FRONT BRACE ☒ NO

MOTOR MOUNT

CHASSIS T-BRACE

FRONT ARMS ☐ MEDIUM ☐ HARD ☒ GRAPHITE

CHASSIS ☐ GRAPHITE ☒ ALU

REAR ARMS ☐ MEDIUM ☐ HARD ☒ GRAPHITE