SET-UP SHEET

XRAY XT8'23 SET-UP VER. 01 ©XRAY

XRAY XT8'24

RACE	TESTING		
TRACK	NOVI		
NAME	TATER SONTAG	DATE	6-14-25

TEMPERATURE AIR	82	TEMPERATURE TRACK	

LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
		/sec	/min

TRACKS

SIZE	☐ OPEN	☐ MEDIUM	☒ TIGHT
TRACTION	☐ LOW	☐ MEDIUM	☒ HIGH
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☒ HARD PACKED	☐ SOFT DIRT	☐ CLAY
	☐ BLUE GROVE	☐ ASTRO TURF	☐ GRASS
CONDITION	☐ DRY	☐ DUSTY	☐ WET ☐ MUD

DIFFERENTIAL

	FRONT	CENTER	REAR	
CASE MATERIAL	G	G	G	CASE MATERIAL
OIL	30	30	25 2G	OIL
CROWN GEAR	KIT		KIT	CROWN GEAR

GEARING

CLUTCH BELL	13 /T	48 /T	SPUR GEAR
SHOE	ALUM SOFT	MEDIUM	SPRING
	ALUM MED	MEDIUM	

SHOCKS

FRONT		REAR
KIT	TYPE	KIT
TRK8768	SPRINGS	TRK6090
EMULSION	MEMBRANE	EMULSION
550 /cSt	OIL	450 /cSt

STD. PISTONS

☒ 6 HOLES	1.1 mm	☐ 6 HOLES
☐ 8 HOLES	1.2 mm	☐ 8 HOLES
☐ 10 HOLES	1.3 mm	☐ 10 HOLES
	1.4 mm	
1.3	OTHER	1.3

VALVE PISTONS

5+2 HOLES	1.5 mm	5+2 HOLES
6+2 HOLES	1.3 mm	6+2 HOLES
	1.4 mm	
8+2 HOLES	1.2 mm	8+2 HOLES
	1.3 mm	

ANTI-ROLL BAR

FRONT		REAR
2.3 /mm	THICKNESS	2.8 /mm

TIRES

FRONT		REAR
HAVOC	BRAND	HAVOC
CLAY ORO	COMPOUND	CLAY ORO
STOCK	INSERTS	STOCK
PM	WHEELS	PM

ENGINE

TYPE	AD3
MUFFLER	2090
MANIFOLD	75
PLUG	O.S P3 GOLD
FUEL	NITROLUX Y3

BODY TYPE	TOTAL WEIGHT
JCON S15	/g

COMMENT







