SET-UP SHEET

SCX'23 SET-UP SHEET VER. 2 ©XRAY 2023

XRAY SCX

RACE	Base Carpet Setup		
TRACK	The Factory RC Raceway		
NAME	Shaun Duffy	DATE	02-06-2025

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK

SIZE	☐ OPEN	☐ MEDIUM	☒ TIGHT
TRACTION	☐ ☐ ☐ ☐ ☐ ☐ ☒ ☐ ☐	VERY-LOW	MEDIUM / VERY-HIGH
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ CLAY	☒ CARPET	☐ ASTRO
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED	☒ DRY
	☐ DUSTY	☐ LOAMY	☐ WET

TRANSMISSION

DIFFERENTIAL	BALL DIFF ☐	☒ GEAR DIFF	OIL 100 cSt	
SATELITE GEARS	COMPOSITE ☐	☐ STEEL	GEARS 2 ☒	☐ 4
SLIPPER	2 PAD ☐	☒ 3 PAD	2 mm	
	ELIMINATOR ☐			

GEARING

PINION	24 T	SPUR GEAR	78 T

SHOCKS

FRONT		REAR
4 dot	SPRINGS	3 dot
450 cSt	OIL	400 cSt
☐ 2 HOLES ●	PISTONS	● 2 HOLES ☐
☒ 3 HOLES ●	☐ ø1.6mm ☒	● 3 HOLES ☒
☐ 6 HOLES ●	☐ ø1.7mm ☐	● 6 HOLES ☐
HOLES ●	ø1.5 mm / ø mm	● HOLES
DOWNSTOP SHIM 0 mm (INSERT UNDER PISTON)		DOWNSTOP SHIM 0 mm (INSERT UNDER PISTON)
LENGTH 25.1 mm		LENGTH mm
UPSTOP SHIM 0 mm (INSERT ABOVE COLLAR)		UPSTOP SHIM 0 mm (INSERT ABOVE COLLAR)
COLLAR STANDARD ☐ -2mm ☐ OTHER -4 collar	KIT BALL JOINT KIT	STANDARD ☐ COLLAR -2mm ☐ -4 collar OTHER

SHOCK TOWER

FRONT	REAR
COMPOSITE ☐ ☒ GRAPHITE	COMPOSITE ☐ ☒ GRAPHITE

ANTI ROLL BARS

REAR	
THICKNESS	1.6 mm

TIRES

FRONT		REAR
Proline Prism	BRAND	Proline Prism
CR3	COMPOUND	CR3
Blue	INSERTS	Blue
DE Racing	WHEELS	DE Racing

ELECTRONICS

MOTOR	Exalt 13.5t	FG RC 160A	SPEEDO
MOTOR TIMING	48	Exalt 5700mah	BATTERY

BODY

Proline Axis

COMMENT

13.2mm '24 Buggy Shocks - Custom Lower Towers - +10g weight in Alu Arm Mount - Custom Rear body mount stabilizer - Active Diff (120 seg) - Exalt Ceramic Bearings - Vented Slipper disks - Black Slipper pad (in middle) - XT2 Solid Arms - '25 Ball Studs & Ends - Ti 3.5mm turnbuckles - Rear Shock Mount Adapter (arrow in)









