SET-UP SHEET

RX8'23 SET-UP SHEET VER. 1 ©XRAY

XRAY RX8'23

RACE	Hudy series -AMSCI
TRACK	Leno
NAME	Nejc Miheli
DATE	18.5.2025

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
3	3	13.887 /sec	/	

TRACKS

TRACK CONDITION	[x] SMOOTH	[ ] MEDIUM	[ ] BUMPY
	[ ] TECHNICAL	[x] MIXED	[ ] FAST
TRACK TRACTION	[ ] LOW	[ ] MEDIUM	[x] HIGH

GEARING

PINION	1ST	17 [ ]	18 [x]	19 [ ]	SPUR	1ST	57 [ ]	58 [ ]	59 [x]	60 [ ]
	2ND	22 [ ]	23 [x]	24 [ ]	25 [ ]	2ND	53 [ ]	54 [x]	55 [ ]	

PULLEY 28 [ ] 29 [x] 30 [ ]

RATIO 1ST [ ] RATIO 2ND [ ]

FRONT	SHOCKS	REAR
7.5	SPRING	smj 6.1
500 cSt	OIL	700 cSt
25 %	REBOUND	25 %
[ ] YES [x] NO	FOAM INSERTS	[ ] YES [x] NO
[x] 2 HOLES [ ] 3 HOLES [ ] OTHER	PISTONS	[x] 2 HOLES [x] 3 HOLES [ ] OTHER
[x] 1.0mm [ ] 1.1mm [ ] 1.2mm		1.0mm [ ] 1.1mm [x] 1.2mm

FRONT	WIRE	REAR
2.3 mm		2.8 mm

FRONT LEFT	FRONT RIGHT	TIRES	REAR LEFT	REAR RIGHT
matrix	handout	MANUFACTURER		
°	°	SHORE /degr.	°	°
mm	mm	DIAMETER	mm	mm
mm	mm	5 MIN. WEAR	mm	mm
		RUBBER TIRES		

ENGINE

ENGINE	MAX rp9	FUEL	mvp		
CARB. DIA /mm	9.0	HEAD CLEARANCE		PLUG	7
MUFFLER	2164	MANIFOLD			

CLUTCH / BRAKE

CLUTCH TYPE	[x] STANDARD	OTHER	
CLUTCH BELL	[ ] STANDARD	[x] ALU	OTHER
CLUTCH SHOE	[x] STANDARD	OTHER	
CLUTCH SPRING	[ ] STANDARD	OTHER	BM
CLUTCH FLY WEIGHT	[x] 3mm Set screw	[ ] 4mm Set screw	[ ] WITHOUT
CLEARANCE /mm	0.6		
SPRING PRELOAD /mm	0.9		
BRAKE PAD	[x] STANDARD	OTHER	
BRAKE DISC	[x] STANDARD	OTHER	

BODY	hyper diabolo

WING	HEIGHT	saw wing +9mm

COMMENTS

RX8'26, SRC ploš ica, max odklon/EPA (cca 37 stopinj),ozek servosaver,uteži na repu avta, slike -start setupa (17.5.2025), dejanske 20.5.2025. AVTO JE BIL OK TUDI Z stabi spredi 2.2, dolgo medosno razdaljo, 260mm širine, pozicija ozkega servosaverja na 2, bumpsteer 3mm in brez kakršnega koli flexa

