SET-UP SHEET

XRAY X10'26 & XP10

RACE	PRO10 Eurocup
TRACK	MRTE
NAME	Alexander Hagberg
DATE	04/07/26


TRACK TEMPERATURE	QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
50	1		13.1 /sec	23 /	5:10

TRACK

TRACK SURFACE		CARPET	☒	ASPHALT	
TRACK LAYOUT	☐	TECHNICAL	☐	MIXED	☒ FAST
TRACTION	☐	LOW	☐	MEDIUM	☒ HIGH

CENTER SHOCK ☐ — CENTER SHOCK DAMPENER — ☐ CENTER TUBE





SHOCK OIL	2000 /cSt	TUBE OIL	/cSt
SHOCK REBOUND	0 /%		

BUMP SPRING



☐ CONICAL-PROGRESSIVE /C

STRAIGHT-LINEAR ☒ /C




SIDE DAMPING



OIL 600 /cSt

TIRES

FRONT		REAR
RUBBER ☐ ☒ FOAM		
Hot Race 37	TIRES	Hot Race 30
56.5	DIAMETER /mm	57.5
Spider Red	ADDITIVE	Spider Red
60	ADDITIVE TIMING	60
8	WIPE OFF TIME	8



TRANSMISSION

GEAR DIFF	SOLID AXLE	BALL DIFF
☐	☐	☒
OIL /cSt		☐ ☐ ☐ ☐ ☒
		LOOSE MEDIUM TIGHT

GEARING (spur) ÷ (pinion) = FDR

SPUR GEAR /T	PINION /T	FINAL DRIVE RATIO
81	14	31mm

ELECTRONICS

MOTOR	HW G3 4.5T
SPEEDO	HW XR10 PRO G3
SERVO	Sanwa PGS-LHR
BATTERIES	Team EAM 7700

BODY

TYPE	Mirage 0.5mm, 148mm height, side wings 28mm above body

COMMENTS

X12 side shocks used, C=1.5 spring. X-stiff rear long bump spring. Front brace - 1x mounted below arm.

