SET-UP SHEET

XB2'26 SET-UP SHEET VER. 1 ©XRAY 2024

XRAY XB2'26

RACE	winter inddor		
TRACK	västerort		
NAME	Edwin Angseryd	DATE	2026-11-08
LAPS		BEST LAP TIME	18,3 sec
QUALIFYING POSITION	1	FINAL POSITION	2

TRACK

SIZE	☐ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	☐ VERY-LOW	☐ MEDIUM	☐ VERY-HIGH
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ CLAY	☒ CARPET	☐ ASTRO
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED	☐ DRY
	☐ GLUED	☐ DUSTY	☐ LOAMY	☐ WET

TRANSMISSION

BALL DIFF ☐ GEAR DIFF ☒ ACTIVE DIFF ☐

DIFFERENTIAL OIL 50k cSt — 60° 90° 120°

SATELITE GEARS COMPOSITE ☐ ☒ STEEL GEARS 2 ☐ ☒ 4

SLIPPER ____ mm ☐ SOLID AXLE

2-PAD SLIPPER CLUTCH PLATES — SLIPPER PADS

VENTILATED ☒ ☐ STANDARD KIT ☒

GEARING

PINION	18t T	SPUR GEAR	78t T

GEAR BOX

TYPE: FRONT LCG 3G ☒ ☐ 5G ☐ REAR 3G LCG — HARDNES: KIT ☒ ☐ GRAPHITE

SHOCKS

FRONT		REAR
4dot	SPRINGS	4dot
300 cSt	OIL	300 cSt
2 HOLES ☒	☒ ø1.6mm ☐ ☐ ø1.8mm ☒	2 HOLES ☒
HOLES ____	ø 2 mm — ø 2 mm	HOLES ____
Previous 0 -1 -1	CAP	Previous 0 -1 -1
Piston 2.0 ☒ ☐ 2.5		Piston 2.5 ☐ ☒ 2.0
KIT ☒ ☐ Precis.		Precis. ☐ ☒ KIT
Downstop shim INSERT UNDER PISTON ____ mm		Downstop shim INSERT UNDER PISTON ____ mm
Length 21 mm		mm 25 Length
Upstop shim INSERT ABOVE COLLAR ____ mm		mm Upstop shim INSERT ABOVE COLLAR
COMP. ☐ 0mm ☐ -2mm ☒ ALU ☒ -4mm ☐ -6mm	COLLAR	0mm ☐ -2mm ☐ COMP. ☒ -4mm ☐ ALU -6mm ☐
+4mm ☐ +2mm ☐ 0mm ☒	BALL JOINT	0mm ☒ +2mm ☐ +4mm ☐

ANTI ROLL BAR

FRONT		REAR
1,2 /mm	THICKNESS	1,4 /mm

TIRES

FRONT		REAR
hot race	BRAND	hotrace
	COMPOUND	
	INSERTS	
	WHEELS	

ELECTRONICS

MOTOR	Hw4,5	hw g3	SPEEDO
SERVO	srt		BATTERY

BODY	TOTAL WEIGHT
kit ☐ LIGHT	/g

COMMENT

FRONT — APPLIED ◉ ☒ APPLIED — REAR

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☒
ALU ☐
STEER. ANGLE SCREW ☐

ALU C-HUB
UP /mm
DOWN /mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRPHITE ☒
ALU ☐

LONGER BUSHINGS
UP ☐
DOWN ☒

CAMBER LINK LOCATION 2 1

SHIM 1mm /mm — 4 3 2 1

LOWER SHOCK POSITION 2 1

UPPER SHOCK POSITION
☒ 6 DOT
☐ 4 DOT
1 2 3 4

SHIM 0mm /mm

DRIVE SHAFT ☒ KIT /mm

SHIM 2mm /mm

SHIM 3mm /mm

LOWER SHOCK POSITION 1 2 3

MEDIUM ☐
HARD ☐
GRAPHITE ☒
ALU ☐

REAR UPRIGHT
HIGH ☐
LOW ☐

1 2 3 4
#325341
ADJ. DRIVE AXLE

ARM MOUNT
0° ☐ KIT
0° ☒ ALU
-3° ☐ ALU
+3° ☐ ALU
0° ☐ BRASS
TOTAL ____ KICK-UP°

FRONT WING KIT ☐ ☐ OTHER
YES ☐ ☒ NO

STEERING BUMP STEER
SHIM 1mm /mm
ACKERMANN SHIM 0mm /mm
CASTER BUSHINGS 0° ☐ 2.5° ☒ 5° ☐

KICK-UP°

ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP

FRONT

Cutting line +/- from the base line.
+/- mm
Wing length /mm
SHOCK TOWER /mm
Offset wing mounting behind the rear shock tower.

WING TYPE
CENTER FIN YES ☐ ☐ NO
WING POSITION
UP ☒
DOWN ☐

FRONT TOE 1 °
OUT
OFFSET kit
WHEELBASE ____ /mm
ROLL CENTER
KIT ☒
ALU ☐

STEERING
PLATE — KIT ☒ ALU ☐
ARMS — KIT ☒ ALU ☐

EXTENSION
1 DOT ☒
2 DOTS ☐
3 DOTS ☐

SERVO BRACE YES ☒ ☐ NO

SERVO POSITION 1 2

REAR TOE ° IN

BATTERY PLACEMENT
LONG SIDE FRONT ☐ ☐ LONG SIDE REAR

MOTOR PLATE 1 DOT-KIT ☒

BATTERY SIZE
☐ STD. SHORT
☐ LOW SHORT

1 2 3 4 5 6 7 8

SIDE BRACES KIT ☒ ☐ GRAPHITE

COOLING FRONT ☐ ☐ REAR

OFFSET kit
WHEELBASE 3 /mm

ROLL CENTER
ALU - KIT ☒
GRAPHITE ☐
COMP. ☐

REAR

REAR
ROLL CENTER SUSPENSION HOLDERS

RR 0.5° ☐ ☐ 1° — XRAY 3° — SHIM ____ /mm SHIM

RF 0.5° ☒ ☐ 1°

RR 0.5° ☐ ☐ 1° — XRAY 1° — SHIM ____ /mm SHIM

FRONT CAMBER 1 /°
GLUING SIDEWALL YES ☐ ☐ NO
FRONT ARM
MEDIUM ☐
HARD ☐
GRAPHITE ☒
ARM TYPE
SHORT - KIT ☐
LONG ☒

RIDE HEIGHT 14 /mm

DIFF HEIGHT

RIDE HEIGHT 14 /mm
RIDE HEIGHT #107763 GAUGE

1 /°
REAR CAMBER
CUTTING PINS
IN ☐ ☐ OUT
NO ☐ ☐ NO
REAR ARM
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ARM TYPE
STANDARD ☒
DISENGAGED ☐

LOWER ECCENTRIC SHOCK BALL
FRONT ☐ ☒ REAR
FRONT ☐ ☒ REAR

ARM MOUNT BALANCE
#293085
HUDY Pure Tungsten Weight - 10g.

BALANCE /g
BALANCE /g
BALANCE /g

4 3 2 1
3G ☒
CHASSIS BRACE
5G ☐
3 2 1

FRONT CHASSIS FLEX

ELECTRONICS PLATE NO ☐ GRAPHITE ☒ WEIGHT ☐

REAR CHASSIS FLEX

SERVO WEIGHT
STANDARD ☐
LOW PROFILE ☒

CHASSIS
KIT ☐ ☐ 2.5mm 2.0mm
MID-SIZE ☐
SHORT ☐
EXTRA SHORT ☐

ARM SHIM front /mm