SET-UP SHEET

XB2'26 SET-UP SHEET VER. 1 ©XRAY 2024

XRAY XB2'26

RACE	Halloween Havoc		
TRACK	RC Madness		
NAME	Andrew Sreckovich	DATE	2026-11-05

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK

SIZE	☐ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	☐ ☐ ☐ ☐ ☐ ☐ ☒ ☐ ☐	VERY-LOW / MEDIUM / VERY-HIGH	
SURFACE	☒ SMOOTH	☐ MEDIUM	☐ BUMPY
TYPE	☐ CLAY	☒ CARPET	☐ ASTRO
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED	☐ DRY
	☐ GLUED	☒ DUSTY	☐ LOAMY	☒ WET

TRANSMISSION

BALL DIFF ☐ GEAR DIFF ☐ ACTIVE DIFF ☐

DIFFERENTIAL — OIL 300k cSt — 60° 90° 120°

SATELITE GEARS — COMPOSITE ☐ ☒ STEEL — GEARS 2 ☒ 4 ☐

SLIPPER ____ mm — ☒ SOLID AXLE

2-PAD SLIPPER CLUTCH PLATES — SLIPPER PADS

VENTILATED ☐ ☐ STANDARD — KIT ☐

GEARING

PINION	32 T	SPUR GEAR	72 T

GEAR BOX

TYPE — HARDNES

FRONT LCG 3G ☒ ☐ 5G ☐ REAR 3G LCG — KIT ☐ ☒ GRAPHITE

SHOCKS

FRONT		REAR
2 Dot	SPRINGS	3 Dot
cSt 450-Gold	OIL	450-Red cSt
2 HOLES ☒	☐ ø1.6mm ☐ ☐ ø1.8mm ☐	2 HOLES ☐
1.8 HOLES	ø VRP mm	ø VRP mm — 2.0 HOLES

CAP — KIT ALU ☒ ALU KIT

Previous Piston 2.0 ☐ ☐ 2.5 KIT ☐ ☐ Precis. — 0 -1 -1

Previous Piston 2.5 ☐ ☐ 2.0 Precis. ☐ ☐ KIT — -1 -1 0

Downstop shim (INSERT UNDER PISTON): 0 mm — 0 mm

Length: 20.0 mm — 26.5 mm

Upstop shim (INSERT ABOVE COLLAR): 2 mm — 3 mm

COLLAR

0mm ☐		0mm ☐
COMP. ☐ -2mm ☒		☐ -2mm ☐ COMP.
ALU ☒ -4mm ☐		☒ -4mm ☒ ALU
-6mm ☐		-6mm ☐

BALL JOINT

☐	☒	☐		☐	☐	☒
+4mm	+2mm	0mm		0mm	+2mm	+4mm

ANTI ROLL BAR

FRONT	THICKNESS	REAR
1.1 /mm		1.3 /mm

TIRES

FRONT		REAR
JC Pin Swag	BRAND	JC Nessi
Pink	COMPOUND	Pink
None	INSERTS	Cut to 4wd siz
JC	WHEELS	JC

ELECTRONICS

MOTOR	Hobbywing C	G3X	SPEEDO
SERVO	Mach-1	Mach-1 6800	BATTERY

BODY

Kit — ☒ LIGHT

TOTAL WEIGHT

/g

COMMENT

FRONT

APPLIED ◉ ☒ APPLIED — REAR

CASTER BLOCK
MEDIUM ☐
HARD ☐
GRAPHITE ☒
ALU ☐
STEER. ANGLE SCREW ☐

ALU C-HUB ⊖
UP /mm
DOWN /mm

STEERING BLOCK
MEDIUM ☐
HARD ☐
GRPHITE ☐
ALU ☐

LONGER BUSHINGS
UP ☐
DOWN ☒

CAMBER LINK LOCATION: 2 1

SHIM ⊖ 3 /mm — 4 3 2 1

LOWER SHOCK POSITION: 2 1

UPPER SHOCK POSITION
6 DOT ☐
4 DOT ☐
1 2 3 4

SHIM ⊖ 0 /mm

DRIVE SHAFT ☐ KIT — SHIM ⊖ 0 /mm

SHIM ⊖ 4 /mm

LOWER SHOCK POSITION: 1 2 3

REAR UPRIGHT
MEDIUM ☐
HARD ☐
GRAPHITE ☐
ALU ☒
HIGH ☐
LOW ☒

1 2 3 4 — #325341 ADJ. DRIVE AXLE

ARM MOUNT
0° ☐ KIT
0° ☒ ALU
-3° ☐ ALU
+3° ☐ ALU
0° ☐ BRASS
TOTAL ____ KICK-UP°

FRONT WING KIT ☒ ☐ OTHER
YES ☐ ☒ NO

STEERING BUMP STEER
SHIM ⊖ 2 /mm
ACKERMANN SHIM 2 /mm
CASTER BUSHINGS 0° ☒ 2.5° ☐ 5° ☐

KICK-UP°

ARM MOUNT 0° + CASTER BUSHING 0° = TOTAL 22° KICK-UP

FRONT

Cutting line +/- from the base line.
+/- mm — Wing length /mm
SHOCK TOWER 0 /mm
Offset wing mounting behind the rear shock tower.

WING TYPE Lush
CENTER FIN YES ☐ ☒ NO
WING POSITION UP ☐ DOWN ☒

FRONT TOE -1 ° — OUT
OFFSET 3
WHEELBASE ⊖ 2 /mm
ROLL CENTER KIT ☐ ALU ☒

STEERING
PLATE KIT ☐ ALU ☒
ARMS KIT ☐ ALU ☒

EXTENSION 1 DOT ☒ 2 DOTS ☐ 3 DOTS ☐
SERVO BRACE YES ☐ ☒ NO
SERVO POSITION 1 2

REAR TOE ° — IN
BATTERY PLACEMENT
LONG SIDE FRONT ☒ — LONG SIDE REAR ☐
MOTOR PLATE 1 DOT-KIT ☒
OFFSET 6
WHEELBASE ⊖ 1 /mm

BATTERY SIZE
☒ STD. SHORT
☐ LOW SHORT

SIDE BRACES KIT ☐ ☒ GRAPHITE

COOLING FRONT ☒ ☐ REAR

1 2 3 4 5 6 7 8

ROLL CENTER
ALU - KIT ☒
GRAPHITE ☐
COMP. ☐

REAR

REAR ROLL CENTER SUSPENSION HOLDERS

RF 0.5° ☐ ☐ 1°

RR 0.5° ☐ ☐ 1° — XRAY 3° — SHIM ⊖ /mm SHIM ⊖

3° 1°

RR 0.5° ☐ ☐ 1° — XRAY 1° — SHIM ⊖ /mm SHIM ⊖

FRONT CAMBER -1 /°
GLUING SIDEWALL YES ☒ ☐ NO
FRONT ARM MEDIUM ☐ HARD ☐ GRAPHITE ☒
ARM TYPE SHORT - KIT ☒ LONG ☐

RIDE HEIGHT 13 /mm — RIDE HEIGHT #107763 GAUGE — 13 /mm RIDE HEIGHT

DIFF HEIGHT
-1 /°

REAR CAMBER
CUTTING PINS IN ☐ ☐ OUT NO ☒ ☒ NO
REAR ARM MEDIUM ☐ HARD ☐ GRAPHITE ☒
ARM TYPE STANDARD ☒ DISENGAGED ☐

SERVO WEIGHT
STANDARD ☐
LOW PROFILE ☒

ARM MOUNT BALANCE
#293085 HUDY Pure Tungsten Weight - 10g.

LOWER ECCENTRIC SHOCK BALL
FRONT ☒ ☐ REAR — FRONT ☐ ☒ REAR

BALANCE /g — BALANCE /g — BALANCE /g

4 3 2 1
3G ☒
CHASSIS BRACE
5G ☐
3 2 1

FRONT CHASSIS FLEX

ELECTRONICS PLATE NO ☐ GRAPHITE ☒ WEIGHT ☐

REAR CHASSIS FLEX

CHASSIS KIT ☐ ☐ 2.5mm 2.0mm
MID-SIZE ☒
SHORT ☐
EXTRA SHORT ☐

ARM SHIM ⊖ /mm