SET-UP SHEET

X4'26 SET-UP SHEET VER.1 ©XRAY

XRAY X4'26

RACE	Toys for tots VTA
TRACK	Ontrack raceway
NAME	Billy Beach
DATE	11/7/26

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
3	3	10.82 /sec	26	5:04

TRACK

TRACK SURFACE		[X] CARPET	[ ] ASPHALT
TRACK LAYOUT	[ ] TECHNICAL	[X] MIXED	[ ] FAST
TRACTION	[ ] LOW	[ ] MEDIUM	[X] HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL: Spool /cSt	[X] FRONT SOLID AXLE	GEAR DIFF OIL: 5k /cSt

UP [ ] [X] DOWN	SOLID & DIFF POSITION	UP [X] [ ] DOWN	
PINION: 54 /T	SPUR GEAR: 82 /T	F. DRIVE RATIO: 2.89	

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.8
350	OIL /Cst	350
0	REBOUND %	0
[ ] 4 HOLES [X] PSS	[ ] 1.1mm [X] 1.2mm	[ ] 1.1mm [ ] 1.2mm
		[ ] 4 HOLES [X] PSS
2x.8		2x.8
SHOCK LENGTH 7.5 /mm		7.5 /mm SHOCK LENGTH

1.3	ANTI-ROLL BAR THICKNESS/mm	1.2

Gravity VTA	TIRES		
Sxt 3.0	ADDITIVE		
5	ADDITIVE TIMING		
	WIPE OFF TIME		
Timing:	Temp.:	TIRE WARMERS Timing:	Temp.:

SIDE WALL GLUE
DIA. First lug /mm

FRONT TIRES
ADDITIVE AREA /mm

TOTAL WEIGHT	/g	WEIGHT BALANCE FRONT %	REAR %

MOTOR		TIMING	
ESC		BATTERIES	
BODY		WING	

BODY POSITION
/mm Dimension from body post to window bottom line
Dimension from body post to upper holder
WING SIDE PLATE YES [ ] NO [ ]
Dimension from edge to surface /mm

WAVE BRACE
TOP DECK [ ]
BULKHEADS [ ]
NONE [X]

GF [ ] 1.6 [ ] 2.0 [X] SCREWS
SHIMS
Rear used in front
2.0 [ ] 1.6
#301092
[X] 2.0 [ ] 1.6 [ ] GF
CUTTING
NONE [ ] BEARING

COMMENTS

FRONT & REAR SUSPENSION

FRONT CASTER 5° 4° 3° — Adjust with eccentric bushings
Upper links CASTER
BUMP STEER 4 /mm
HEIGHT /mm
SHIM 4 /mm
SHIM 3 /mm
0.5° 1.5° 2.5° 3.5° 4.5° 5.5° — Adjust with eccentric bushings
Upper links CASTER

2 /mm FF [X]
5.2 /mm RIDE HEIGHT
FR 2 /mm [X]
[X] SERVO SAVER
[ ] SERVO HORN
TOE GAIN 2 /mm
2 /mm RF [X]
5.5 RIDE HEIGHT
RR 2 /mm [X]

FRONT

1 /degr. CAMBER Left=Right
BODY STOP YES [ ] NO [X] /mm
SHIM /mm 3
FF 2 / FR 2 SHIMS /mm 2
FRONT HUB MEDIUM [X] GRAPH. [ ] HARD [ ] ALU
#107730 Droop Gauge
#107712
DOWNSTOP /mm
Set with shocks [ ] Set without shocks
YES [X] NO [ ] YES [X] NO [ ] SUSPENSION FLEX SCREW
DRIVE SHAFT 58mm [X] 59mm [ ]
SHIM /mm .5
UPSTOP /mm
DROOP /mm
Set with shocks [ ] Set without shocks

REAR

1 /degr. CAMBER Left=Right
BODY POST VERTICAL [X] HORIZONT. [ ]
SHIM /mm 3
RF 0 / RR 0 SHIMS /mm 2.5
REAR HUB MEDIUM [X] GRAPH. [ ] HARD [ ] ALU
#107712
DOWNSTOP /mm
Set with shocks [ ] Set without shocks
YES [X] NO [ ] YES [X] NO [ ] SUSPENSION FLEX SCREW
DRIVE SHAFT 52mm [ ] 54mm [X]
SHIM /mm .5
UPSTOP /mm
DROOP /mm
Set with shocks [ ] Set without shocks

FRONT TOP VIEW REAR

1 TOE OUT Left=Right
ACKERMANN 0 /mm
SHORT LiPo BRASS WEIGHT YES [ ] NO [X] YES [ ] NO [X]
2 TOE IN Left=Right
40g
BRASS WEIGHT FOR MOTOR MOUNT
40g
UPPER CLAMP KIT [X] -1mm [ ]
UPPER CLAMP FLEX
UPPER CLAMP FLEX
UPPER CLAMP KIT [X] -1mm [ ]
SHIMS /mm
FRONT UPPER
CFF™ ARM - S [X]
LINKS SHORT [ ]
LINKS LONG [ ]
STEERING BRIDGE YES [ ] NO [ ]
STEERING SHIM SIZE
PLATE 8.0mm KIT [X] 7.5mm [ ]
REAR UPPER
CFF™ ARM - S [X]
LINKS SHORT [ ]
LINKS LONG [ ]
HUB OFFSET
SHIM /mm 1.5
HUB OFFSET
SHIM /mm

FRONT BOTTOM VIEW REAR

BUMPER
3D - KIT [X]
FOAM [ ]
STEER. LOCK /degr.
T-BRACE ALU [ ] BRASS [ ]
SERVO HOLDER
MOTOR MOUNT
CHASSIS T-BRACE
FRONT ARMS MEDIUM [X] HARD [ ] SHORT [ ]
CHASSIS GRAPHITE [ ] ALU [ ] ALU 1.5mm [ ]
REAR ARMS MEDIUM [X] HARD [ ] SHORT [ ]