SET-UP SHEET

X4'25 SET-UP SHEET VER.1 ©XRAY

XRAY X4'25

RACE	Canadian Nats 25.5 LMH TQ Raine Gorman			
TRACK	Seaway mall			
NAME	Raine Gorman	DATE	4/9-4/12	

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
1	2	8.4 /sec	/	

TRACK

TRACK SURFACE		[X] CARPET	[ ] ASPHALT
TRACK LAYOUT	[ ] TECHNICAL	[ ] MIXED	[X] FAST
TRACTION	[ ] LOW	[X] MEDIUM	[ ] HIGH

TRANSMISSION

FRONT			REAR	
GEAR DIFF OIL	/cSt	[X] FRONT SOLID AXLE	GEAR DIFF OIL	6k /cSt
PINION	48 /T	SPUR GEAR	88 /T	FINAL DRIVE RATIO

SHOCKS

FRONT		REAR
2.4-2.7	XRAY SPRINGS	2.6
425	OIL /Cst	425
0	REBOUND %	0
[ ] YES [X] NO	FOAM INSERTS	[ ] YES [X] NO
[X] 4 HOLES [ ] PSS	[ ] 1.1mm [X] 1.2mm	[ ] 1.1mm [X] 1.2mm / [ ] 4 HOLES [X] PSS
SHOCK LENGTH 7.5 /mm		7.5 /mm SHOCK LENGTH

ANTI-ROLL BAR

1.2	THICKNESS/mm	1.2

Gravity Gold	TIRES	Gravity Gold
SXT 3.0	ADDITIVE	SXT 3.0
5 minutes	ADDITIVE TIMING	5 minutes
1 min	WIPE OFF TIME	1 min
Timing:	TIRE WARMERS	Timing:
Temp.:		Temp.:

SIDE WALL GLUE DIA. 57 /mm

FRONT TIRES ADDITIVE AREA Full /mm

TOTAL WEIGHT	1325 /g	WEIGHT BALANCE	FRONT 51 %	REAR 49 %

MOTOR	Orca 25.5	TIMING	45
ESC	TZ-01 ESC	BATTERIES	Zombie 6200
BODY	SR LMH body	WING	SR

BODY POSITION

54.5 /mm Dimension from body post to window bottom line

5th hole +O rings

Dimension from body post to upper holder

WING SIDE PLATE [ ] YES [X] NO

Dimension from edge to surface /mm

X4'23 / Rear used in front: GF [ ] 1.6mm [X] / [ ] 2.0mm [ ] / [X] 1.6mm [ ] GF — SCREWS — SHIMS

X4'22: 2.0mm [ ] / 1.6mm [ ] — NONE [ ] / BEARING [ ]

TOP DECK CUTTING

COMMENTS

Droop 3 over ride height front
3 over ride height rear

FRONT & REAR SUSPENSION

FRONT CASTER: [ ] [X] [ ] — 5° 4° 3° — Adjust with eccentric bushings

Upper links CASTER [ ]

BUMP STEER 1.5 /mm

HEIGHT Top /mm

SHIM 2.5 /mm

REAR CASTER: [ ] [X] [ ] [ ] [ ] [ ] — 0.5° 1.5° 2.5° 3.5° 4.5° 5.5° — Adjust with eccentric bushings

Upper links CASTER [ ]

2 /mm	FF	5.2 /mm RIDE HEIGHT	FR	2 /mm	[X] SERVO SAVER [ ] SERVO HORN	TOE GAIN 0.5 /mm	2.5 /mm	RF	5.3 /mm RIDE HEIGHT	RR	2.5 /mm

FRONT

2 /degr. CAMBER — Left=Right

BODY STOP YES [X] NO [ ] /mm

SHOCK HOLDERS SHIM 4 /mm

FF 2.5 /mm FR 2.5 /mm SHIM 2.5 /mm

FRONT HUB: MEDIUM [ ] HARD [X] GRAPHITE [ ] ALU [ ]

SHIM 0.5 /mm

SHOCK TOWER SCREW: YES [X] NO [ ] / YES [X] NO [ ]

DRIVE SHAFT: 58mm [X] 59mm [ ] — BEARING [X] BLADE [ ]

Notes /mm DOWNSTOP

#107702 Chassis Droop Gauge Blocks — #107712 Chassis Droop Gauge

Set with shocks [X] Set without shocks [ ]

REAR

2 /degr. CAMBER — Left=Right

BODY POST VERTICAL [ ] HORIZONT. [X]

SHOCK HOLDERS FIXED [X] ACTIVE [ ] SHIM 4 /mm

RF 2 /mm RR 2 /mm SHIM 2.5 /mm

REAR HUB: MEDIUM [ ] HARD [X] GRAPHITE [ ] ALU [ ]

SHIM 1 /mm

SHOCK TOWER SCREW: YES [X] NO [ ] / YES [X] NO [ ]

DRIVE SHAFT: 52mm [ ] 54mm [X] — BEARING [X] BLADE [ ]

Notes /mm DOWNSTOP

#107702 Chassis Droop Gauge Blocks — #107712 Chassis Droop Gauge

Set with shocks [X] Set without shocks [ ]

FRONT TOP VIEW REAR

1 TOE OUT Left=Right

2.25 TOE IN Left=Right

ACKERMANN SHIM /mm

SHORT LiPo BRASS WEIGHT YES [ ] NO [X] / YES [ ] NO [X]

DIFF POSITION: UP [ ] DOWN [X] +1mm [ ]

BRASS WEIGHT FOR MOTOR MOUNT

24 40g — 5 40g

FRONT UPPER ARM LINKS: C [ ] XS [ ] S [ ] M [X]

STEERING BRIDGE YES [ ] NO [X]

STEERING SHIM /mm SIZE — PLATE [X] 8.0mm STD. [ ] 7.5mm

SHIM 0 /mm

REAR UPPER ARM LINKS: C [ ] XS [ ] S [ ] M [X]

HUB OFFSET [ ] [ ] [X] SHIM /mm

FRONT BOTTOM VIEW REAR

BUMPER: 3D - KIT [X] FOAM [ ]

STEER. LOCK 25 /degr.

T-BRACE: ALU [ ] BRASS [ ]

MOTOR MOUNT

SERVO HOLDER

CHASSIS T-BRACE

FRONT ARMS: MEDIUM [ ] HARD [X] GRAPHITE [ ]

CHASSIS: GRAPHITE [ ] ALU [X] ALU 1.5mm [ ]

REAR ARMS: MEDIUM [ ] HARD [X] GRAPHITE [ ]