SET-UP SHEET

X12'26 SET-UP SHEET VER.1 ©XRAY

XRAY X12'26

RACE	Strickland Club race
TRACK	Strickland RC Park
NAME	Barry Oathout
DATE	0712/26

QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME
4	na	13.985 /sec	21 /	5:11

TRACK

TRACK SURFACE	☐ CARPET	☒ ASPHALT	
TRACK LAYOUT	☐ TECHNICAL	☒ MIXED	☐ FAST
TRACTION	☐ LOW	☐ MEDIUM	☒ HIGH

CENTER SHOCK DAMPENER

CENTER SHOCK OIL		CENTER SHOCK REBOUND	
450 /cSt		0	/%

REAR BUMP SPRING

☐ CONICAL-PROGRESSIVE /C

☐ STRAIGHT-LINEAR Gold /C

SIDE DAMPING

OIL 15,000 /cSt

FRONT	TIRES	REAR
Excellerate	TIRES TYPE	Excellerate
new	DIAMETER /mm	new
Paragon	ADDITIVE	Paragon
5 min	ADDITIVE TIMING	immediately after last race
right before	WIPE OFF TIME	right before



TRANSMISSION


BALL DIFF	GEAR DIFF	SOLID AXLE
☐	☐	☐
☐ LOOSE ☐ ☐ ☒ MEDIUM ☐ TIGHT	OIL /cSt	

GEARING

PINION / T	51	SPUR GEAR/T	73
FINAL DRIVE RATIO		ROLLOUT	

ELECTRONICS

MOTOR	Fantom	SERVO	Exalt HB112
SPEEDO	Tekin Rs	BATTERIES	Tekin 8500



BODY

TYPE	
Bittydesigns Agata	

I added .5mm to bump steer changed to Gold side springs They didnt spay the track, but sprayed it the night before track temp was 130

COMMENTS

